

Bondline 300

Thermal Adhesive Tape



Bondline 300 is a thermally conductive double-sided adhesive tape formed from a thin polymer coated with thermal adhesive on both sides.

Bondline 300 is designed to attach two surfaces that require a strong, permanent bond, excellent thermal connection and guaranteed electrical insulation up to 65000 volts. **Bondline 300** offers a high performance thermal solution for bonding heat generating electronics to a heatsink, cold wall or chassis.

Features

- Double-sided, thermal adhesive tape consisting of a KAPTON polyimide film and silicone rubber
- Delivers excellent electrical isolation in combination with good thermal connection
- Pressure sensitive application improving to maximum bond strength after 24 hours

Availability

- Available in standard thickness of 0.12mm
- Supplied on 30m rolls in varying widths
- Available kiss-cut on rolls and as die-cut custom shapes

Benefits

- Removal of micro air voids between mating surfaces reduces thermal resistance
- Extremely thin bond line of 0.12mm for improved thermal performance
- High dielectric strength for demanding electronic applications

Recommended Uses

- Bonding PCBs and FR4s to a heatsink
- To cool devices in power supplies or power converters
- High voltage breakdown applications

Typical Physical Properties

Property (unit)	Test Method	Bondline 300
Colour	Visual	Light Brown
Thermal Conductivity (W/mK)	ASTM D5470	0.40
Thickness (mm)	Visual	0.12
Thermal Resistance @ 10 PSI (°C in ² /W)	ASTM D150	0.10
Operating Temp (°C)	In House	-20 to +150

Mechanical and Electrical Properties

Property (unit)	Test Method	Bondline 300
Flammability	UL 94	HB
Adhesion to Steel (N/cm)	ASTM 412	3.25
Breakdown Voltage (VAC)	ASTM D149	>6000
Shelf Life (months)	Visual	6



www.universal-science.com

UK +44 (0) 1908 222 211 NL +31 (0) 35 5239 209
 IT +39 (02) 395 613 61 FR +33 (0) 1602 00276
 USA +1 440 382 1077



This material is often used in these industries:



Information furnished by Universal Science regarding technical data is believed to be accurate and reliable but our customers bear the responsibility in assessing fitness for purpose. Universal Science makes no warranties as to the fitness, merchantability or suitability of any materials or products for any uses. Universal Science shall not be liable for damages of any kind. Universal Science terms and conditions of sale apply.